

Ultipor® GF Plus Series Filter Elements

Description

Ultipor® GF Plus filters have a pleated high area construction for long service life. The medium uses a binder resin which coats the glass fibers, imparting a positive zeta potential in aqueous service. The resin also bonds the glass fibers to a polyester substrate, producing a rugged composite medium. Applications for such filters are numerous as most suspensions are negatively charged in aqueous solution, including not only particles but bacteria and viruses. Some Ultipor GF Plus filter grades efficiently remove sub-microscopic haze from a wide variety of pharmaceuticals and cosmetics, including colognes.

Ultipor GF Plus filters have a fixed pore construction which precludes unloading or media migration.

Ultipor GF Plus elements with polypropylene hardware in a double open-ended UNI CAP configuration are rated to withstand differential pressures of 5.2 bard (75 psid) @ 38°C (100°F) and 3.1 bard (45 psid) @ 82°C (180°F).

When constructed in a single open-ended AB configuration, the element can withstand differential pressures of 5.2 bard (75 psid) @ 27°C (80°F) and 3.8 bard (55 psid) up to 82°C (180°F).



Ultipor GF Plus Filter

Removal ratings

| Cartridge Grade | Liquid Service ³ Rating in Microns at % Efficiency | | Aqueous Clean Pressure Drop Per 25.4 cm (10 in) Module (MBARD/LPM) / (PSID/GPM) ⁴ | Typical Aqueous Flow Per 25.4 cm (10 in) Cartridge (LPM/GPM) |
|-----------------|--|--------|--|--|
| | 99% | 99.98% | | |
| U010Z | 0.6 ² | 1 | 3.09 / 0.17 | 7.6 - 11.4 / 2-3 |
| U2-20Z | 0.8 ² | 2 | 2.55 / 0.14 | 7.6 - 11.4 / 2-3 |
| U030Z | 2.0 | 3 | 1.82 / 0.10 | 7.6 - 11.4 / 2-3 |
| U6-40Z | 3.2 | 6 | 0.91 / 0.05 | 11.4 - 18.9 / 3-5 |
| U100Z | 6.0 | 10 | 0.55 / 0.03 | 11.4 - 18.9 / 3-5 |
| U200Z | 17.0 | 20 | 0.36 / 0.02 | 11.4 - 18.9 / 3-5 |
| U400Z | 25.0 | 40 | 0.27 / 0.015 | 15.1 - 26.5 / 4-7 |

Ordering Information

DOE - Pall Part Number = PUY 1 2 3

SOE - Pall Part Number = AB 1 2 4 5

Table 1

| Code | Cartridge lengths (cm/in) |
|------|---------------------------|
| 10 | 25.4 / 10 |
| 20 | 50.8 / 20 |
| 30 | 76.2 / 30 |
| 40 | 102 / 40 |

Table 2

| Code | Cartridge |
|--------|-----------|
| U010Z | U010Z |
| U2-20Z | U2-20Z |
| U030Z | U030Z |
| U6-40Z | U6-40Z |
| U100Z | U100Z |
| U200Z | U200Z |
| U400Z | U400Z |

Table 3

| Code | Gasket option |
|------|--------------------------|
| J | Ethylene propylene (std) |
| H13 | Nitrile |
| H | Fluorocarbon elastomer |

Table 4

| Code | End Fittings | |
|------|--------------------------|-------------------------|
| | O-ring fitting I.D. (In) | O-ring replacement size |
| 3, 8 | 1 ¼ | -222 |
| 7 | 1 ½ | -222 |

Table 5

| Code | O-ring option |
|------|------------------------|
| JH4 | Silicone |
| H | Fluorocarbon elastomer |
| J | Ethylene propylene |

Housing Information

Housings are available in either polypropylene, carbon steel, or stainless steel and can accommodate 1 to 152, 10 in modules per housing.



Pall Corporation

Fuels and Chemicals

25 Harbor Park Drive
Port Washington, NY 11050
+1 516 484 3600 telephone
+1 888 873 7255 toll free US

Portsmouth - UK
+44 (0)23 9230 3303 telephone
+44 (0)23 9230 2507 fax
processuk@pall.com



Visit us on the Web at www.pall.com

Pall Corporation has offices and plants throughout the world. For Pall representatives in your area, please go to www.pall.com/contact.

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid.

© Copyright 1989, 2011, Pall Corporation. Pall,  and Ultipor are trademarks of Pall Corporation. ® indicates a trademark registered in the USA. *Filtration. Separation. Solution.SM* and **ENABLING A GREENER FUTURE** are service marks of Pall Corporation.