HARDWARE

ELECTRICAL | MILLWORK

| PAINT **PLUMBING** **FLOORCOVERINGS**

THANK YOU FOR CHOOSING AAAA AAIDWEST UltraDeck®

Click here to track your order status!



Quality decking is our specialty.

Click Here to view the Full Installation Guide

Framing

Make sure the subframe is dry and properly blocked to reduce twisting or excess shrinkage. UltraDeck® has a 16" maximum on-center joist spacing. Since UltraDeck® is a nonload-bearing product, the framing of the structure needs to support large items, like hot tubs or large bar/ grill areas. Be sure to review local building codes on all aspects of your construction.

Gapping

gapping both on the sides and ends. UltraDeck® T-Clips™ or UltraClips® will automatically set side-to-side gapping, making installation quicker and easier. End gapping should be done by the "end gapping chart" found in the installation instructions.

All composite decking will expand and contract to some degree, and it will need proper

Wherever two boards meet, additional nailer boards must be installed. Both ends of the deck

Nailer Boards >

boards will need to be fastened using T-Clips™ or DekMount Brackets at the joint as well.

Watch our helpful T-Clip[™] video for a detailed guide on installation. Boards must be securely

T-Clip Installation ▶

fastened on both sides of every joist with approved fastener methods.

UltraDeck® Fusion® and Rustic™ Railings should have spindles installed on the outside

Railing Installation >

edge of the railing. Therefore, accurate measurements are mandatory when building railing sections. Railing support blocks are also required for any railing exceeding a 3' width.

Storage and Handling

Proper storage of UltraDeck® will help your decking and railing stay beautiful. Store UltraDeck® in a clean, dry space. Remember to store it flat and use multiple spacers so

they're no further than 2' apart.

Installation Instructions

to install it properly will void the warranty.

Read through the UltraDeck® installation instructions before installing your decking. Failure

warranty could be voided. Please read and follow all instructions and guides.

WARNING: Installation of UltraDeck® must be done per the installation instructions or

CONNECT WITH US

EMAIL PREFERENCES





For additional questions, email us at UltraDeckHelp@midwestmanufacturing.com







STORE LOCATOR