GetStoreRegisterInfo

Returns a list of registers with current operating details from a specified store.

Request Syntax

```
GET /StoreRegisterStatus?storeId={storeId}&limit=20 HTTP/1.1
```

URI Request Parameters

This request uses the following URI parameters:

URI	Description	Required?
storeId	The global ID of the requested store.	**Yes**
limit	Limits the amount of registers to be returned. Default is 20.	No

---

Request Body

This request does not include a request body.

Response Elements

Name	Description	Type
length	The total registers in this response.	integer
id	The name of this register.	string

Name	Description	Type
osVersion	The operating system version for this register.	string
lastLogin	Unix timestamp of the last local login.	integer
lastUser	The username of the last local login.	string
inUse	If the machine is actively being used.	boolean

Example

```
HTTP/1.1 200
Content-type: application/json
{
    "length": 20,
    {
        "id":"hb0487",
        "osVersion":"3.21.8464",
        "lastLogin":1646559705,
        "lastUser":"jsmith",
        "inUse": false,
    }
    ...
}
```

Errors

ParamInvalid

At least one of the parameters in the request is invalid.

HTTP Status Code: 400

NotFound

The resource does not exist.

HTTP Status Code: 404

TooManyRequests

Too many requests have been sent in a given time.

HTTP Status Code: 429

Related

GetRegisterCache

RebootRegister