

Enable Device Logs

Enable logging and the Syslog Aggregator.

Configure RAM Memory Logging as follows:

- Emergency, Alert, and Critical: **Enable**
- Error, Warning, Notice, Informational, and Debug: **Disable**

Configure Flash Memory Logging as follows:

- Emergency and Alert: **Enable**
- Critical, Error, Warning, Notice, Informational, and Debug: **Disable**

Copy the running configuration file to the startup configuration file using the following settings:

- Source File Name: **Running configuration**
- Destination File Name: **Startup configuration**

Small Business Save cisco Language: English Logout About Help

SG 300-28P 28-Port Gigabit PoE Managed Switch

- Getting Started
- Status and Statistics
- Administration
- System Settings
- Console Settings
- Management Interface
- IPv4 Interface
- IPv6 Global Configuration
- IPv6 Interface
- IPv6 Addresses
- IPv6 Default Router List
- IPv6 Tunnel
- IPv6 Neighbors
- IPv6 Routes
- User Accounts
- Idle Session Timeout
- Time Settings
- System Log
 - Log Settings
 - Remote Log Servers
- File Management
- Reboot
- Diagnostics
 - Discovery - Bonjour
 - Discovery - LLDP
 - Discovery - CDP
 - Ping
 - Traceroute

Log Settings

✔ Success.

Logging: Enable

Syslog Aggregator: Enable

Max. Aggregation Time: sec. (Range: 15 - 3600, Default: 300)

RAM Memory Logging	Flash Memory Logging
Emergency: <input checked="" type="checkbox"/>	Emergency: <input checked="" type="checkbox"/>
Alert: <input checked="" type="checkbox"/>	Alert: <input checked="" type="checkbox"/>
Critical: <input checked="" type="checkbox"/>	Critical: <input type="checkbox"/>
Error: <input type="checkbox"/>	Error: <input type="checkbox"/>
Warning: <input type="checkbox"/>	Warning: <input type="checkbox"/>
Notice: <input type="checkbox"/>	Notice: <input type="checkbox"/>
Informational: <input type="checkbox"/>	Informational: <input type="checkbox"/>
Debug: <input type="checkbox"/>	Debug: <input type="checkbox"/>

http://192.168.0.2/cs7cb50969/home.htm SG 300-28P 28-Port Gigabit Poe Smart Switch

- Getting Started
- Status and Statistics
- Administration
- System Settings
- Console Settings
- Management Interface
- IPv4 Interface
- IPv6 Global Configuration
- IPv6 Interface
- IPv6 Addresses
- IPv6 Default Router List
- IPv6 Tunnel
- IPv6 Neighbors
- IPv6 Routes
- User Accounts
- Idle Session Timeout
- Time Settings
- System Log
 - Log Settings
 - Remote Log Servers
- File Management
 - Copy/Save Configuration
 - Upgrade/Backup Firmware
 - Active Image
 - Download/Backup Configuration Files
 - Configuration Files Properties
 - DHCP Auto Configuration
- Reboot
- Diagnostics
 - Discovery - Bonjour
 - Discovery - LLDP
 - Discovery - CDP
 - Ping

Please note: navigation to other screens while copy operation is in progress will abort the process.

Please note: the running configuration file which is volatile and is not retained between reboots. You must copy the running configuration file to the startup configuration file after you have completed all your changes.

Backup configuration: Backup configuration

Sensitive Data: Exclude Encrypted Plaintext

Available sensitive data options are determined by the current user's SSD rules

Save Icon Blinking: Enabled

© 2010-2014 Cisco Systems, Inc. All Rights Reserved.